

In the Claims:

1.(currently amended)        A cutting template to be used for cutting a plurality of meat pieces from a meat section all of which are precisely similar in size and weight, said cutting template comprising:

      a graspable handle composed of a planar forefinger abutting section and a planar thumb rest section which are separated by a crease, said forefinger abutting section being deflected at said crease at an angle to said thumb rest section;

      a guide plate integrally attached to said thumb rest section at an elongated lineal bend ~~graspable handle~~, said guide plate being elongated and extending transversely from said thumb rest section ~~graspable handle~~; and

      a first guide bar attached to said guide plate directly adjacent said lineal bend ~~template~~ and extending outwardly from said ~~[[first]]~~ guide plate, whereby said guide plate is to be placed against an edge of the meat section with said first guide bar resting on an upper surface of the meat section with the operator to then move a cutting instrument around an exterior edge of said guide bar to cause severing of a first said meat piece with the procedure to then be repeated to obtain other said meat pieces.

Amendment to CUTTING TEMPLATE FOR CUTTING MEAT PIECES

Zachary A. Lundin, inventor

Serial No. 10/613,134

Filed July 3, 2003

Page 5 of 9

2.(original) The cutting template as defined in Claim 1 wherein:

means for fixing a position of said guide bar connected to said guide bar, whereby said means causes said guide bar to be fixed in position on a section piece prior to severing of said meat piece.

3.(original) The cutting template as defined in Claim 2 wherein:

said means comprising a structure that impales the meat section.

4.(original) The cutting template as defined in Claim 3 wherein:

said means comprising a row of sharply pointed sawteeth mounted on said guide bar.

5.(original) The cutting template as defined in Claim 1 wherein:

said guide bar encloses an open space which is closed at one side by said guide plate and closed at the opposite side by said guide bar, during severing of a meat portion the meat portion is to be located directly adjacent said open space.

6.(original) The cutting template as defined in Claim 1 wherein:

there being included a second guide bar which is connected to said first guide bar with said second guide bar enclosing an additional open space with said additional open space being substantially identical in size to said open space.

Amendment to CUTTING TEMPLATE FOR CUTTING MEAT PIECES

Zachary A. Lundin, inventor

Serial No. 10/613,134

Filed July 3, 2003

Page 6 of 9

7.(original) The cutting template as defined in Claim 6 wherein:

said second guide bar being attached to said first guide bar by a cutting instrument guide.

8.(original) The cutting template as defined in Claim 7 wherein:

means for fixing the position of said first guide bar and said second guide bar on the meat section.

9.(original) The cutting template as defined in Claim 8 wherein:

said means comprising a structure that impales the meat section.

10.(original) The cutting template as defined in Claim 9 wherein:

said means comprises a row of sharp pointed sawteeth being mounted on said second guide bar.

11.(new) The cutting template as defined in Claim 1 wherein:

said angle comprising ten to fifteen degrees.